

RS-1775 Ultra Short-Depth Cube



Features

- Intel Core 2 Quad / Core 2 Duo / Celeron 400 Sequence processors (Conroe-L)
- Two DDR2 Sockets, Supports up to 4GB
- Two SATA 3Gb/s ports & One e.SATA 3.0 Gb/s port
- One External Slim Optical, One Internal 3.5", & One Internal 2.5" Bay
- Standard-length Expansion Cards Support
- SFX 300W with 80 PLUS Certification
- 8.74"W x 6.93"H x 10.87"D

FEATURES	
Motherboard	LGA775 Intel® Core™ 2 Quad Mini-ITX Motherboard
Processor	Intel® Core™ 2 Quad / Core 2 Duo / Celeron 400 Sequence processors (Conroe-L)
System Memory	Two DDR2 sockets, up to 4GB DDR SDRAM 667/800MHz DDRII SDRAM, w/o ECC
Expansion Slots	1 x PCI Express (x16)
Onboard Graphics	NVIDIA GeForce GTS 250 Core Edition
Drive Bays	1 x Slim optical External 1 x 3.5" Internal 1 x 2.5" Internal
I/O Interface	Front: 2 x USB 2.0 ports 1 x Audio 1 x MIC
Cooling System	Front- 1 x 120 mm intake fan 1200 rpm Side- Oversized vents Top- Oversized vents
Dimensions	222 mm (W) x 176 mm (H) x 276 mm (D)
Construction	Plastic front panel, SECC body
Storage	2 x SATA 3Gb/s ports 1 e.SATA 3.0 Gbps port SATA RAID 0, 1
Power Supply	SFX 300W with 80 PLUS certification (SilverStone tuned)
System Environment	Operating Temperature: 5° to 40°C (41° to 104°F) Non-operating Temperature: -20° to 80°C (-4° to 176°F) Relative Humidity: 10% to 90% (non-condensing)